

AD-A177 947

THE DECOMPOSITION OF AN ARBITRARY THREE-DIMENSIONAL
PLANAR POLYGON INTO A SET OF CONVEX POLYGONS(U) NAVAL
POSTGRADUATE SCHOOL MONTEREY CA J H POTTS DEC 86


1/1

UNCLASSIFIED

F/G 12/1

ML

IND
4-5/
DHC



XEROCOPY RESOLUTION TEST CHART

AD-A177 947

NAVAL POSTGRADUATE SCHOOL
Monterey, California



DTIC
ELECTE
MAR 20 1987
S D

THESIS

THE DECOMPOSITION
OF AN ARBITRARY THREE-DIMENSIONAL
PLANAR POLYGON INTO A
SET OF CONVEX POLYGONS

by

Jeffrey H. Potts

December 1986

Thesis Advisor:

Michael J. Zyda

Approved for public release; distribution is unlimited.

DTIC FILE COPY

87 3 12 001

unclassified

SECURITY CLASSIFICATION OF THIS PAGE

APR 11 9:11

REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION unclassified			1b RESTRICTIVE MARKINGS	
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.	
2b DECLASSIFICATION/DOWNGRADING SCHEDULE				
4 PERFORMING ORGANIZATION REPORT NUMBER(S)			5 MONITORING ORGANIZATION REPORT NUMBER(S)	
6a NAME OF PERFORMING ORGANIZATION Naval Postgraduate School		6b OFFICE SYMBOL (If applicable) 52	7a NAME OF MONITORING ORGANIZATION Naval Postgraduate School	
6c ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000			7b ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000	
8a NAME OF FUNDING/SPONSORING ORGANIZATION		8b OFFICE SYMBOL (If applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c ADDRESS (City, State, and ZIP Code)			10 SOURCE OF FUNDING NUMBERS	
			PROGRAM ELEMENT NO	PROJECT NO
			TASK NO	WORK UNIT ACCESSION NO
11 TITLE (Include Security Classification) THE DECOMPOSITION OF AN ARBITRARY THREE-DIMENSIONAL PLANAR POLYGON INTO A SET OF CONVEX POLYGONS				
12 PERSONAL AUTHOR(S) Potts, Jeffrey H.				
13a TYPE OF REPORT Master's Thesis		13b TIME COVERED FROM TO	14 DATE OF REPORT (Year, Month, Day) 1986 December	15 PAGE COUNT 77
16 SUPPLEMENTARY NOTATION				
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Computer graphics; polygons; polygon decomposition; polygon concavity.	
19 ABSTRACT (Continue on reverse if necessary and identify by block number)				
<p>We present in this study a three step algorithm for the decomposition of arbitrary, three-dimensional, planar polygons into convex polygons. Through a series of translations and rotations, an arbitrary polygon is mapped onto the x-y plane, then broken into a set of convex polygons, and finally mapped back to the polygon's original coordinate system for filling and display by special graphics hardware.</p>				
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21 ABSTRACT SECURITY CLASSIFICATION unclassified	
22a NAME OF RESPONSIBLE INDIVIDUAL Prof. Michael Zyda			22b TELEPHONE (Include Area Code) (408) 646-2305	22c OFFICE SYMBOL Code 522k

Approved for public release; distribution is unlimited.

**The Decomposition
Of An Arbitrary Three-Dimensional Planar Polygon
Into A Set Of Convex Polygons**

by

Jeffrey Hal Potts
Captain, United States Marine Corps
B. S., United States Naval Academy, 1977

Submitted in partial fulfillment of the
requirements for the degree of


MASTER OF SCIENCE IN COMPUTER SCIENCE

from the


NAVAL POSTGRADUATE SCHOOL

December 1986


Author:



Jeffrey H. Potts

Approved by:


Michael J. Zyda, Thesis Advisor


Robert B. McGhee, Second Reader


Vincent Y. Lum, Chairman,
Department of Computer Science


Kneale T. Marshall,
Dean of Information and Policy Sciences

ABSTRACT

We present in this study a three step algorithm for the decomposition of arbitrary, three-dimensional, planar polygons into convex polygons. Through a series of translations and rotations, an arbitrary polygon is mapped onto the x-y plane, then broken into a set of convex polygons, and finally mapped back to the polygon's original coordinate system for filling and display by special graphics hardware.



Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

TABLE OF CONTENTS

I. INTRODUCTION	6
II. BACKGROUND	7
A. DEFINITIONS	7
B. DECOMPOSITION	7
C. RESEARCH FACILITIES	9
III. STEP I: MAPPING THE 3D POLYGON TO THE 2D X-Y PLANE	12
A. THE NORMAL TO A POLYGON	12
B. ANGLES ABOUT THE AXES	14
C. TRANSFORMATION MATRIX	16
IV. STEP II: POLYGON DECOMPOSITION	18
A. CLOCKWISE ORDERING	18
B. VERTEX EXAMINATION	19
1. Test One	19
2. Test Two	19
3. Test Three	22
C. SELECTION COMPLETION	24
V. STEP III: MAPPING TO THE ORIGINAL COORDINATE SYSTEM ..	26
VI. IRIS IMPLEMENTATION	27
A. MATRIX IMPLEMENTATION	27
B. DOUBLY LINKED LIST	27
C. VERTICES STACK	28
VII. LIMITATIONS AND CONCLUSIONS	30
LIST OF REFERENCES	33

APPENDIX - ALGORITHM SOURCE CODE	34
INITIAL DISTRIBUTION LIST	76

I. INTRODUCTION

Computer hardware advancements applied to the field of computer graphics have recently made possible the real-time display and animation of three-dimensional object models. In most currently produced graphics systems, the three-dimensional (3D) object models are comprised of sets of 3D polygons. For years the key bottleneck to generating real-time images of 3D models has been the limited speed with which the 3D polygons comprising the model have been filled. This bottleneck has been alleviated recently with the advent of special hardware designed to fill polygons at rates exceeding 44 million pixels per second [Ref. 1]. For real-time animation of 3D object models, such polygon fill rates are essential.

The majority of the graphics systems that provide polygon fill hardware only provide hardware for filling convex polygons. Concave polygons passed to such hardware usually are filled incorrectly, if at all. To utilize the capabilities of such hardware for the general polygon case, that is, a mix of concave and convex polygons, it is necessary to have some means of decomposing an arbitrary 3D planar polygon into a set of 3D planar convex polygons completely covering the area defined by the original polygon. The following study attempts to provide such an algorithm. We then discuss the implementation and performance characteristics of that algorithm on the Silicon Graphics, Inc. IRIS workstation.

II. BACKGROUND

A. DEFINITIONS

A polygon is defined as a geometric figure that is described by an array of x, y, and z coordinates for its vertices. A two dimensional polygon lying in the x-y plane is a special case of a three dimensional polygon in which the z coordinates are all zero. A convex polygon is one that has no points of negative curvature along its boundary [Ref. 2: p. 217]. This means that a line can be drawn from any point inside the polygon to any of its vertices and have the line lie entirely within the polygon boundary [Ref. 3: p. 350]. A concave polygon fails the above test, i.e. we cannot draw a line from every point inside the polygon to every vertex and have the line remain within the polygon boundary. However, any point inside a concave polygon can be shown to lie inside a convex polygon created by some of the vertices and sides of the original polygon [Ref. 3: p. 330]. Figure 2.1 provides examples of convex and concave polygons.

B. DECOMPOSITION

To fill a concave polygon utilizing hardware that only correctly fills convex polygons, we must first break down the polygon into simpler convex polygons that together cover the area of the original. The process of decomposing a concave polygon does not necessarily yield a single unique set of convex polygons, but the




Figure 2.1 - Convex and Concave Polygons




Figure 2.2 - Two Equivalent Decompositions
of a Concave Polygon.

result of two different decompositions of the same polygon should be equivalent as shown in Figure 2.2.

During the operation of decomposing a polygon, there are two main checks that must be conducted to ensure complete and proper decomposition takes place. The first check is to ensure that no area of a created convex polygon falls outside the boundary of the original concave polygon. The second check is to ensure that the concave polygon is completely covered by the total areas of the created convex polygons. Figure 2.3 provides examples of the two checks.

The polygon decomposition algorithm produced for this study is comprised of three basic steps. The first maps the three dimensional coordinates of the polygon into a two dimensional plane. This process generates a polygon that is more easily examined and decomposed. The second step conducts the actual decomposition and performs the two decomposition checks. The third step maps the coordinates of the created convex polygons back to the original orientation in three-space. At this point, the created convex polygons are then ready for passing to the graphics system's polygon fill hardware.

C. RESEARCH FACILITIES

The IRIS (Integrated Raster Imaging System) 2400 Graphics Workstation, manufactured by Silicon Graphics, Inc., is the target system for our polygon decomposition algorithm. By incorporating custom VLSI chips to replace slower graphics software, the IRIS system can accept polygons in user-defined




Figure 2.3a - Without a check to ensure the convex polygon does not fall outside the bounds of the original polygon, vertices could be chosen that yield an incorrect decomposition.




Figure 2.3b - The second decomposition check ensures the concave polygon is completely covered by the decomposed polygons. In this case all vertices and edges were utilized, however a hole is still left.

coordinates, and transform them to screen coordinates for display on a color graphics monitor that provides 1024 x 768 resolution. This use of special hardware yields processing speeds that are some 100 times faster than similar operations carried out in software.

III. STEP I: MAPPING THE 3D POLYGON TO THE 2D X-Y PLANE

A. THE NORMAL TO A POLYGON

The first step of the polygon decomposition algorithm, is comprised of several small steps. The goal of these steps is to map the polygon to the x-y plane. First, three non-colinear points are selected from the array of x, y, and z coordinates of the polygon. These are used to define the equation of the plane for the 3D polygon, and the normal to that plane (Figure 3.1).

$$Ax + By + Cz = D$$

$$\vec{N} = A\vec{i} + B\vec{j} + C\vec{k}$$


The coefficients A, B, and C are calculated from the coordinates of the three selected points by the following equations:

$$A = (y_0 - y_1)(z_2 - z_1) - (y_2 - y_1)(z_0 - z_1);$$

$$B = (z_0 - z_1)(x_2 - x_1) - (z_2 - z_1)(x_0 - x_1);$$

$$C = (x_0 - x_1)(y_2 - y_1) - (x_2 - x_1)(y_0 - y_1).$$

The coefficients are then used to solve for D of the equation of the plane.



Three vertices 0, 1, and 4
are selected to determine the
Normal to the plane.

Figure 3.1 The Normal to a Polygon

B. ANGLES ABOUT THE AXES

Once the equation of the plane is determined, each point in the polygon input array is checked to ensure that the polygon is in fact planar. If the polygon passes this test, then the angles between the normal and the axes of the coordinate system are found. From these angles, the necessary rotations, about the x and y axes, to bring the polygon into the x-y plane, are calculated. The following equations [Ref. 4: pp. 24-59] are used to calculate the angles shown in Figure 3.2a.

$$\cos \alpha = \frac{A}{\sqrt{A^2 + B^2 + C^2}}$$

$$\cos \beta = \frac{B}{\sqrt{A^2 + B^2 + C^2}}$$

$$\cos \gamma = \frac{C}{\sqrt{A^2 + B^2 + C^2}}$$

For the polygon to lie in the x-y plane, the angle between the normal and the z axis is either zero or 180 degrees. Necessarily then rotations are conducted to bring the angles between the normal and the x and y axes to 90 degrees each.

First a projection of the normal onto the x-z plane is made as shown in Figure 3.2b. The dot product of that projected normal \vec{N}' and the z axis is calculated. The dot product is divided by the product of the magnitudes of the two vectors yielding the cosine of the angle of rotation about the y axis (ϕ).






Figure 3.2 Angles about the Axes

$$\cos \phi = \frac{\vec{N} \cdot \vec{Z}}{|\vec{N}| |\vec{Z}|}$$

A second projection of the normal onto the y-z plane is made and the angle of rotation about the x axis (θ) is calculated in the same manner as above (Figure 3.2c).

C. TRANSFORMATION MATRIX

To actually rotate the polygon into the x-y plane, a transformation matrix must be created that is used in the multiplication of the polygon's coordinates. We first translate the polygon to the origin by adding the negative x, y, and z coordinates of one of the polygon's vertices. Assuming l, m, and n are the coordinates selected, the matrix becomes:

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ -l & -m & -n & 1 \end{bmatrix}$$

A rotation matrix for the angle ϕ about the y axis is then created

$$\begin{bmatrix} \cos \phi & 0 & \sin \phi & 0 \\ 0 & 1 & 0 & 0 \\ -\sin \phi & 0 & \cos \phi & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

and concatenated with the translation matrix. This is followed by a multiplication with a rotation matrix for the angle θ about the x axis.

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos\theta & -\sin\theta & 0 \\ 0 & \sin\theta & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

The result of these matrix concatenations is the following transformation matrix that is used to map the array of vertices onto the x-y plane.

$$\begin{bmatrix} \cos\phi & -\sin\phi\sin\theta & -\sin\phi\cos\theta & 0 \\ 0 & \cos\theta & \sin\theta & 0 \\ \sin\phi & \cos\phi\sin\theta & \cos\phi\cos\theta & 0 \\ -l\cos\phi - n\cos\phi & m\cos\theta + (l\sin\phi - n\cos\phi)(-\sin\theta) & -m\sin\theta + (l\sin\phi - n\cos\phi)(\cos\theta) & 1 \end{bmatrix}$$

Once we have this matrix set up, call it $M_{to\text{plane}}$, we then use it to transform the polygon's coordinates via a simple row vector by matrix multiplication. The result of this multiplication is a transformed set of coordinates, in which the z coordinates are zero. The x and y values of this transformed array are then used in the decomposition step of our algorithm. We note at this point that for the mapping of the coordinates back to the original vertices (Step III of the Alg.), that the index into the transformed array is also the index for the untransformed point in the original array of vertices.

IV. STEP II: POLYGON DECOMPOSITION

The decomposition step divides the polygon into multiple convex polygons. In so doing, the algorithm performs the two checks to ensure that no area outside the polygon is shaded and that the created convex polygons completely cover the area of the concave polygon. This step requires that the vertices of the polygon be ordered in a clockwise fashion, with respect to the +z directed normal to the x-y plane. Thus a determination of the ordering must be made and if necessary the array of vertices reversed.

A. CLOCKWISE ORDERING

To determine if the vertices of the polygon are ordered clockwise, the polygon's area is calculated using the formula [Ref. 5: p. 369] below. (Note x_i, y_i are the polygon's 2D coordinates.)

$$\frac{1}{2}((x_0y_1) + (x_1y_2) + \cdots + (x_{n-1}y_n) + (x_ny_0) - (y_0x_1) - (y_1x_2) - \cdots - (y_{n-1}x_n) - (y_nx_0))$$

The above equation yields a negative area for clockwise and a positive area for counterclockwise polygons. If the polygon is ordered counterclockwise then the array of x, y, and z coordinates that define the polygon is reversed before the selection procedure is begun.

B. VERTEX EXAMINATION

The selection of vertices for a convex polygon is conducted by examining each vertex of the concave polygon with respect to the previously selected vertices of the developing convex polygon. This is begun by initially selecting two adjacent vertices, then in clockwise order, examining each of the polygon's remaining vertices to build as large a convex polygon as will fit within the boundary of the concave polygon.

A series of tests are conducted in the selection of vertices for the convex polygon. As vertices are selected, the line segments connecting these become the edges of the convex polygon and define its boundary.

1. Test One

The first test of a vertex is if it lies to the left or right of each line segment of the developing convex polygon. The vertices of the concave polygon are examined in clockwise order. Thus if a vertex lies to the left of any of the line segments of the developing polygon, then a concave angle is necessary to include the vertex in the polygon. As shown in Figure 4.1a, vertex 2 lies to the left of the line segment 0-1. A concave angle (ρ in Figure 4.1b) is necessary to add vertex 2 to the developing polygon. Therefore vertex 2 is not selected and the process moves on to perform the same test on vertex 3.

2. Test Two

A vertex that passes the first test may still require a concave angle to be included in the developing convex polygon. In Figure 4.2, the vertices 0, 1, 2, 3,




Figure 4.1 - (a) Vertex 2 lies to the left of the line segment 0-1, (b) Concave angle (ρ) would be required to connect Vertex 2 to the developing polygon, (c) Vertex 2 is skipped and the examination is continued with vertex 3.




Figure 4.2 - (a) Vertex 5 lies to the right of each line segment of the developing polygon, (b) Concave angle (ρ) is required to connect Vertex 5 to Vertex 0, (c) Concave angle (ρ) can be identified since 0 lies to the left of line segment 4-5, (d) Vertex 4 is skipped and the test repeated with line segment 3-5, (e) Vertex 3 is skipped and the test repeated with line segment 2-5, (f) Result of the tests are that vertices 0, 1, 2 and 5 are selected.

and 4 have been previously selected for a convex polygon with vertex 5 under examination. Vertex 5 passes the first test since it lies to the right, or inside of each of the line segments. However, a concave angle (ρ in Figure 4.2b) is again required to connect vertex 5 with vertex 0 of the developing polygon. A concave angle of this type is identified, as shown in Figure 4.2c, if the initial vertex of the developing convex polygon lies to the left of the line segment created by the vertex under examination and the last selected vertex of the developing polygon. In Figure 4.2c, the initial vertex, 0, lies to the left of line segment 4-5. To remedy this, the last selected vertex of the developing convex polygon, vertex 4, is removed and the test is again conducted with the line segment formed by the vertex under examination and the last selected vertex (Figure 4.2d & 4.2e). This process is repeated, removing vertices from the developing polygon, until the initial vertex no longer lies to the left of a new line segment.

3. Test Three

The third test conducted is to ensure that no line segment created in the convex polygon intersects any of the edges of the concave polygon. Such an occurrence results in area outside the concave polygon being included in the convex polygon and an inaccurate polygon fill taking place. In Figure 4.3, the previously selected vertices are 0, 1, 2, and 3. Vertex 7 is under examination and passes the two earlier tests. However, the selection of vertex 7 results in the convex polygon 0, 1, 2, 3, 7 which contains area outside the concave polygon. A situation such as this is identified since line segment 3-7 intersects line segment




Figure 4.3 - Tests must be conducted for the intersection of developed line segments with the edges of the original concave polygon. Otherwise Vertex 7 would be an acceptable vertex for inclusion in the developing polygon 0, 1, 2, 3...

13-0 of the concave polygon. When this occurs, the vertex under examination is removed from the convex polygon and the next vertex of the concave polygon is examined.

C. SELECTION COMPLETION

The selection process for the developing convex polygon concludes when all vertices of the concave polygon have been examined. The convex polygon is then ready for the third step of our algorithm, mapping to the original polygon's 3D coordinates. Figure 4.4 is an example of a concave polygon that was decomposed to the three shaded convex polygons using the above three tests. We have a "hole" left in the concave polygon even though all vertices and edges of the concave polygon have been utilized. Holes such as this are prevented by taking the initial and last vertices of a developed convex polygon as the starting vertices of a convex polygon to be developed. In Figure 4.4, vertices 0 and 2 of polygon 0, 1, 2 are taken to develop convex polygon 0, 2, 4 to fill in the "hole". Once this is accomplished, step two of the algorithm is repeated by selecting a vertex of the concave polygon that has not yet been utilized in a convex polygon. The decomposition process is complete when there are no vertices or edges of the concave polygon that have not been utilized in one or more convex polygons.




Figure 4.4 - All vertices and edges of the polygon have been used, yet a hole remains.

V. STEP III: MAPPING TO THE ORIGINAL COORDINATE SYSTEM

The second and third steps of the decomposition process are interleaved, i.e., each created convex polygon is immediately mapped back to the original coordinate system. This is accomplished by maintaining the original array of vertices that the user provided for the three-dimensional polygon. As a convex polygon is produced, it is actually represented by the indices of its vertices. Actual vertex coordinates are extracted from the vertex array, as required, using the index. In this manner, the transformed coordinates can be utilized during decomposition and the index can be used to obtain the original coordinates for final display. By this method, there is no consequential need to translate and rotate the vertices back to the original coordinate system.

VI. IRIS IMPLEMENTATION

Implementation of the decomposition algorithm on the IRIS system is via approximately 1600 lines of C code (Appendix). Several data structures and various IRIS system hardware features are utilized as described below.

A. MATRIX IMPLEMENTATION

In the development of the transformation matrix, IRIS system calls for translation and rotation are used to alter the top of the system matrix stack. These routines perform the matrix concatenations needed to translate and rotate the polygon to the x-y plane. To convert the polygon vertices to 2D coordinates, four vertices at a time are loaded into a matrix. The x, y, and z coordinates go into the first three columns with 1's filling the fourth column to provide the necessary homogeneous coordinates. This is placed on the system's matrix stack and multiplied with the transformation matrix using the IRIS's Geometry Engines. The transformed coordinates are removed from the matrix stack and the process is repeated until all vertices have been transformed.


B. DOUBLY LINKED LIST

A data structure for each vertex of the polygon is maintained in our system. This structure contains the vertex's index into the vertex array. As actual coordinates are needed, the vertex's index is used to extract the x, y, and z

coordinates from this array. A "used" flag indicates the vertex's use in a developed convex polygon, with a slope and y-intercept stored for the line segment the vertex forms with its predecessor in the array. A forward pointer connects the structure with the next vertex in clockwise order, while a back pointer connects the structure with its preceding vertex. This produces a doubly linked circular list of vertex structures that permits forward clockwise traversal of the polygon and rearward counterclockwise traversal (Figure 6.1).

C. VERTICES STACK

To manage the examination and selection of vertices for a developing convex polygon, a stack is utilized. The size of the vertices stack is determined at run time when contiguous memory is dynamically allocated, based on the number of vertices in the concave polygon. As a vertex is examined, its index is placed on top of the stack along with the slope and y-intercept of the line segment it creates with the vertex below it. If the vertex passes all selection tests, it remains on the stack and a new vertex is pushed on top. On the other hand, when a vertex fails a selection test, it is popped off the stack and the next vertex to be examined is placed on top. Once the selection of vertices for a convex polygon is completed, the vertices are passed to the IRIS system hardware and the stack is cleared to continue with the decomposition process.



(a) Doubly linked circular list of structures,

Rearward Pointer	Index	Used Flag	Slope	Y-intercept	Forward Pointer
---------------------	-------	--------------	-------	-------------	--------------------

(b) Vertex structure

Figure 6.1

VII. LIMITATIONS AND CONCLUSIONS

This study has presented an algorithm for the decomposition of an arbitrary, planar polygon into a set of convex polygons, thus eliminating the need to manually perform such decomposition. With the algorithm's dynamic allocation of memory, the size polygon that can be filled is limited only by the amount of memory available for use. The algorithm indirectly provides an extended capability over the IRIS system's limit of 384 vertices in one polygon (Ref. 6: p. 2).

However due to the time required to test each vertex for concavity, the algorithm is not suggested for use where real-time response is important. To demonstrate the overhead involved in testing for concavity, a convex polygon was filled and displayed 500 times by the algorithm. The same polygon was then filled utilizing only the IRIS's polygon fill hardware. The results are provided in Figure 7.1 for various polygon sizes.

Due to the three primary steps necessary for decomposition and the tests conducted on each vertex, the speed of the algorithm depends entirely upon the number of vertices and concave angles of the polygon. As such, the success of the algorithm's use in real-time display and animation is based upon a balance between the complexity of the concave polygons used and the speed requirements. We suggest that the created concave polygons be computed once and saved.




Figure 7.1 - Time required to fill and display 500 convex polygons with the number of vertices indicated

For IRIS usage, this is perhaps best accomplished through the use of the "object" mechanism of the IRIS graphics library.

LIST OF REFERENCES

1. Silicon Graphics Inc., Marketing Brochure, 1984.
2. Pavlidis, Theo. **Structured Pattern Recognition**, Springer-Verlag, 1977.
3. Pavlidis, Theo. **Algorithms for Graphics and Image Processing**, Computer Science Press, 1972.
4. Rogers, David F., **Mathematical Elements for Computer Graphics**, Kingsport Press, 1976.
5. Shelby, Samuel, **Standard Mathematical Tables**, CRC Press, Inc., 1974.
6. Silicon Graphics Inc., **IRIS User's Guide**, Version 2.4, Document Number 5001-051-001-1, 1986.

APPENDIX - ALGORITHM SOURCE CODE

```
.....
globals.h
.....

= include <gl.h>
= include <device.h>
= include <stdio.h>
= include <math.h>

.....

GLOBAL CONSTANTS
.....

= define NULL 0
= define BOTTOM 0
= define new(x) (x *) malloc(sizeof(x))

.....

GLOBAL TYPES
.....

typedef int boolean;

/* Define a structure to contain data about a vertex of the polygon.
   These structures will be used to create a linked list. */

typedef struct point {
    struct point *back;
    int index;
    float slope;
    Coord intercept;
    int direction;
    boolean failed;
    boolean segment_used;
    struct point *forward;
};

typedef struct point point;
```

/* Define a structure for storing data about each vertex. This will
be used to create a stack for later use. */

```
typedef struct stack {  
    int    index;  
    float  slope;  
    Coord  intercept;  
    int    direction;  
};
```

```
typedef struct stack Stack;
```

```
.....  
GLOBAL DATA STRUCTURES AND VARIABLES  
.....
```

```
Stack  *stack;
```

```
point  *start ptr, *current ptr;
```

```
int    TOP;
```

```
boolean clockwise error flag;
```

```
*****
ROUTINE: convert.c
*****
```

This routine takes the initial array of vertices, passed by the user, and makes the calls to other routines to perform the necessary translation and rotations to transform the array into the x-y-0 plane. This new array is then used by the decomposer to breakdown the polygon into convex polygons.

```
*****
```

```
cpolf(total pts, pts)
```

```
int total pts;
```

```
Coord pts 3;
```

```
{
int pt1, pt2, pt3, cnt;
float A, B, C, D, anglex, angley, anglez, *new_pts;
Matrix transform1;
Matrix points;
```

```
stack = (Stack *) calloc(total pts - 1, sizeof(Stack));
```

```
*****
dynamically allocate memory to create an array to hold the
vertices of the newly transformed polygon.
*****
```

```
new_pts = (float *) calloc(3*total pts, sizeof(float));
```

```
*****
get 3 non-colinear vertices from the polygon to be used for
calculating the normal to the polygon.
*****
```

```
extract 3 pts(total pts, pts, &pt1, &pt2, &pt3);
```

```
*****
calculate the coefficients for the equations to the plane
of the polygon and the normal to that plane.
*****
```

```
determine coeffs(total pts, pts, pt1, pt2, pt3, &A, &B, &C, &D);
```

```

.....
check to ensure all vertices of the polygon lie in the same
plane. If so then calculate the necessary angles of rotation
.....

```

```

if(planar_polygon(total_pts, pts, A, B, C, D)) {

```

```

.....
calculate the rotation about the y axis necessary to
bring the normal into the y-z plane.
.....

```

```

    angles_from_normal(A, B, C, 'y', &anglex, &angley);

```

```

.....
create the transformation matrix necessary to multiply
with the array of vertices to generate the rotation.
.....

```

```

    build_transform_matrix(transform1, angley, 'y', pts, pt1);

```

```

.....
perform the matrix multiplication with the array of
vertices and store the new coordinates in the new array
new_pts.
.....

```

```

    map_pts(total_pts, pts, transform1, points, new_pts);

```

```

.....
now extract three non-colinear vertices from the new
array of vertices, new_pts.
.....

```

```

    extract_3_pts(total_pts, new_pts, &pt1, &pt2, &pt3);

```

```

.....
since the polygon has been rotated about the y axis we
calculate the coefficients for the equations to the
polygon one more time.
.....

```

```

    determine_coeffs(total_pts, new_pts, pt1, pt2, pt3, &A, &B, &C, &D);

```



```
.....  
calculate the rotation about the x axis  
.....
```

```
angles from normal(A, B, C, 'x', &anglex, &angley):  
.....
```

```
.....  
create the transformation matrix  
.....
```

```
build transform matrix(transform1, anglex, 'x', new_pts, pt1):  
.....
```

```
.....  
perform the matrix multiplication  
.....
```

```
map pts[total pts, new_pts, transform1, points, new_pts]:  
.....
```

```
call the routine which will perform the decomposition  
upon the newly transformed polygon which now lies in the  
x-y-0 plane.(thus to be handled as a 2D polygon)  
.....
```

```
split(total_pts, new_pts, pts):  
.....
```

```
.....  
once the dynamically allocated memory for the array  
new_pts has served its purpose, the memory is freed.  
.....
```

```
cfree(new_pts, 3*total_pts, sizeof(float));  
cfree(stack, total_pts, sizeof(Stack));  
  
}
```

```
.....  
if not planar then the decomposition is not attempted.  
.....
```

```
return;
```

```
*****
ROUTINE: extract.c
*****
```

```
This routine searches the array of vertices to find three points which
do not lie on the same line and returns the indices of these points
*****
```

```
extract 3 pts(total pts, pts, pt1, pt2, pt3)
```

```
int total pts;
```

```
Coord pts[3];
```

```
int *pt1, *pt2, *pt3;
```

```
{
```

```
int count, finished;
```

```
*pt1 = 0; *pt2 = 0; *pt3 = 0; count = 0; finished = 0;
```

```
* The first vertex in the array (index = 0) is selected for the first point. *
```

```
while(count < total pts && !finished) {
```

```
* We then search the rest of the array of vertices to locate two more *
```

```
count = 1;
```

```
if(*pt2 == 0) {
```

```
* If the second point has not been selected yet then we check that
x, y, and z coordinates, of the vertex currently under exam, are
different. *
```

```
if(pts[*pt1][0] != pts[count][0]
```

```
pts[*pt1][1] != pts[count][1]
```

```
pts[*pt1][2] != pts[count][2] )
```

```
* If so then the vertex becomes the second point. *
```

```
*pt2 = count; }
```

```
else if(*pt3 == 0) {
```

```
* If the third point has not yet been selected, then we check that
the coordinates of the vertex under examination are different
from both the first and second point. *
```

```
if((pts[*pt1][0] != pts[count][0]
```

```
pts[*pt1][1] != pts[count][1]
```

```

    pts[*pt1][2] != pts[count][2] ) &&
    (pts[*pt2][0] != pts[count][0]
    pts[*pt2][1] != pts[count][1]
    pts[*pt2][2] != pts[count][2] ))
    /* If the coordinates are different then the vertex is selected
       as the third point. */
    *pt3 = count; }

else
    finished = 1;

}

return;

}

```

```
*****
ROUTINE: is_planar.c
*****
```

This routine takes each vertex of the polygon and uses it to solve the equation for the plane as calculated earlier. If every vertex lies in the plane, then a value of 1 is returned.

```
*****
planar_polygon(total pts, pts, A, B, C, D)
```

```
int total pts;
```

```
Coord pts[3];
```

```
float A, B, C, D;
```

```
{
```

```
int count, planar;
```

```
count = 0; planar = 1;
```

```
while(count < total pts && planar) {
```

```
    * The equation for the plane is setup to equal zero if the coordinates
    * of the vertex lies in the plane. A range of .02 on either size of
    * zero is allowed to handle round off error. This test is done for
    * each vertex in the polygon. If any vertex fails the test then the
    * function returns (0) for non-planar. *
```

```
    if((A*(pts[count][0]) - B*(pts[count][1]) - C*(pts[count][2]) - D) > .02
        || (A*(pts[count][0]) - B*(pts[count][1]) - C*(pts[count][2]) - D) < -.02)
        planar = 0;
```

```
    count++;
```

```
}
```

```
return(planar);
```

```
}
```

```
.....
ROUTINE: coeffs.c
.....
```

This routine uses the three vertices selected from the polygon to calculate the coefficients that will be used in both the equation of the plane the polygon lies in and the normal to that plane.

```
.....
```

```
determine_coeffs(total pts, pts, pt1, pt2, pt3, A, B, C, D)
```

```
int total pts;
```

```
Coord pts 3;
```

```
int pt1, pt2, pt3;
```

```
float *A, *B, *C, *D;
```

```
float x0, x1, x2, y0, y1, y2, z0, z1, z2;
```

```
x0 = pts[pt1][0];
```

```
y0 = pts[pt1][1];
```

```
z0 = pts[pt1][2];
```

```
x1 = pts[pt2][0];
```

```
y1 = pts[pt2][1];
```

```
z1 = pts[pt2][2];
```

```
x2 = pts[pt3][0];
```

```
y2 = pts[pt3][1];
```

```
z2 = pts[pt3][2];
```

```
*A = (y0-y1)*(z2-z1) - (y2-y1)*(z0-z1);
```

```
*B = (z0-z1)*(x2-x1) - (z2-z1)*(x0-x1);
```

```
*C = (x0-x1)*(y2-y1) - (x2-x1)*(y0-y1);
```

```
*D = (*A)*pts[pt1][0] + (*B)*pts[pt1][1] + (*C)*pts[pt1][2];
```

```
return;
```

```
*****
ROUTINE: angles.c
*****
```

This routine utilizes the coefficients, determined from the normal to the polygon, to determine the angles of rotation necessary about the x and y axes. These rotations are necessary to bring the polygon into the x-y plane. This routine is called the first time to calculate the rotation about the y axis. The second time it is called is to determine the x axis rotation. The parameter "axis" is used to pass which angle is to be calculated.

```
angles from normal(A, B, C, axis, anglex, angley)
```

```
float A, B, C;
```

```
char axis;
```

```
float *anglex, *angley;
```

```
{
```

```
float pi, degx, degy, degz;
```

```
pi = 3.1415926536;
```

```
degx = acos(A / sqrt(A*A + B*B + C*C)) * 360 / (2*pi);
```

```
degx = acos(B / sqrt(A*A + B*B + C*C)) * 360 / (2*pi);
```

```
degz = acos(C / sqrt(A*A + B*B + C*C)) * 360 / (2*pi);
```

```
if(A == 0 && B == 0) {
```

```
    * simply translate the polygon to the origin *
```

```
    *anglex = 0.0;
```

```
    *angley = 0.0; }
```

```
else if(A == 0 && C == 0) {
```

```
    * rotate polygon 90 degrees about x axis *
```

```
    *anglex = 90.0;
```

```
    *angley = 0.0; }
```

```
else if(B == 0 && C == 0) {
```

```
    * rotate polygon 90 degrees about y axis *
```

```
    *anglex = 0.0;
```

```
    *angley = 90.0; }
```

```
else {
```

```
    * must calculate amount of rotation about the x & y axes *
```

```
    *anglex = acos(C / sqrt(B*B + C*C)) * 360 / (2*pi);
```

```
    *angley = acos(C / sqrt(A*A + C*C)) * 360 / (2*pi);
```

```

if(axis == 'y') {
    if(degx ~ 90.0)
        *angley = -(*angley);
    *anglex = 0.0; }
else {
    if(degy ~ 90.0) {
        *anglex = -(*anglex);
        *angley = 0.0; }
    }
}

```

```

    * convert the angles into tenths of degrees as needed by the IRIS system.
*anglex = 10*(*anglex);
*angley = 10*(*angley);

```

```

return;

```

```
.....
ROUTINE: transmatx.c
.....
```

```

This routine takes a matrix structure and initializes it to an identity
matrix. Then the necessary translation values and rotation values are
added to the matrix to create the resultant transformation matrix.
.....
```

```
build transform matrix(transform1, angle, axis, pts, pt1)
```

```
Matrix transform1;
```

```
float angle;
```

```
char axis;
```

```
Coord pts[3];
```

```
int pt1;
```

```

{
    int i, j;

    * create the identity matrix *
```

```
    for(i = 0; i < 4; i = i + 1) {
```

```
        for(j = 0; j < 4; j = j + 1) {
```

```
            if(i == j)
```

```
                transform1[i][j] = 1;
```

```
            else
```

```
                transform1[i][j] = 0;
```

```
        }
```

```
    }
```

```
    pushmatrix();
```

```
    loadmatrix(transform1);
```

```
    * add in the rotation values *
```

```
    rotate((int)angle, axis);
```

```
    * add in the translation values *
```

```
    translate(-pts[pt1][0], -pts[pt1][1], -pts[pt1][2]);
```

```
    getmatrix(transform1);
```

```
    popmatrix();
```

```
    return;
```

```
}
```


.....
 ROUTINE: mapover.c

This routine places up to 4 vertices into a matrix at one time then performs a matrix multiplication with the transformation matrix to produce x, y, and z coordinates for the polygon that is translated and rotated some amount about the x and y axes. These new coordinates are restored in the array new_pts for further manipulation.


```
map(pt, total_pts, pts, transform1, points, new_pts)
```

```
int total_pts;
Coord pts[3];
Matrix transform1, points;
float new_pts[3];
```

```
int count, count2, cnt;
```

```
count = 0; count2 = 0;
```

```
while(count < total_pts){
```

```
    cnt = 0;
```

```
    while(cnt < 4){
```

```
        * place the coordinates of a vertex into the matrix *
```

```
        points[cnt] = pts[count];
```

```
        points[cnt+1] = pts[count+1];
```

```
        points[cnt+2] = pts[count+2];
```

```
        points[cnt+3] = 1.0;
```

```
        if(count < 1) total_pts =
```

```
            cnt + 1;
```

```
        else
```

```
            break;
```

```
    }
```

```
        * save the state of the matrix stack and perform the multiplication *
```

```
        pushmatrix();
```

```
        loadmatrix(transform1);
```

```
        multmatrix(points);
```

```
        getmatrix(points);
```

```

popmatrix():

cnt = 0;

while(cnt < 4) {
    * move the newly calculated coordinates back into the vertices array *
    new_pts[count2-0] = points[cnt-0];
    new_pts[count2-1] = points[cnt-1];
    new_pts[count2-2] = points[cnt-2];

    if((count2-1) == count)
        cnt = 1;
    else
        break;

}

return;
}

```

.....
ROUTINE: split.c
.....

This routine takes the array for the transformed polygon and calls the necessary functions and routines to decompose the polygon and pass the vertices of the convex polygons to the IRIS system for filling.
.....

split(tota. pts, pts, old. pts)

int total.pts;

Coord pts[3];

Coord old.pts[3];

Object decompose_polygon;
Object whole_thang;
boolean clockwise;
point *p1, *p2;

.....
Create the doubly linked circular list, "main chain", for the concave polygon represented by the pts array. Also initialize flags and ptrs that will be used in decomposing the polygon.
.....

clockwise = clockwise_ordering(tota. pts, pts);

create_main_chain(clockwise, total.pts, pts);

.....
Decompose the main polygon and build the set of simple convex polygons
.....

decompose_polygon(tota.pts, pts, old.pts);

return;

```
*****
ROUTINE:          main_chain.c
*****
```

```
Create the doubly linked circular list, "main chain", for the
concave polygon represented by the pts array. Also initialize
flags and ptrs that will be used in decomposing the polygon.
*****
```

```
create_main_chain(clockwise, total_pts, pts)
```

```
boolean clockwise;
```

```
int    total_pts;
```

```
Coord pts[3];
```

```
{
```

```
int count1;
```

```
point *p1, *p2;
```

```
    * allocate memory for a structure to contain data on the first
      vertex of the polygon *
```

```
p1 = new(point);
```

```
    * set pointers to this structure and initialize all values *
```

```
start_ptr = p1;
```

```
current_ptr = p1;
```

```
p1->index = 0;
```

```
p1->direction = 0;
```

```
p1->failed = FALSE;
```

```
p1->segment_used = FALSE;
```

```
    * if polygon vertices are ordered clockwise then we index the vertices
      array beginning at 0 and incrementing from there. Other we must begin
      at the other end of the vertices array to extract our coordinates. In
      this way a forward move along our doubly linked list will equal a
      clockwise move around the polygon. *
```

```
if(clockwise)
```

```
    count1 = 1;
```

```
else
```

```
    count1 = total_pts - 1;
```

```
    * for each vertex of the polygon we build a point structure, calculate
      the slope, intercept, initialize flags and connect the structure
      via pointers to its preceeding and succeeding vertices in the
```

```

polygon. The result is a doubly linked list of structures. *
do
    p2 = new(point);
    p1->forward = p2;
    p2->back = p1;
    p1 = p2;
    p1->index = count1;
    determine_slope(pts p1->back->index 0, pts p1->back->index 1,
        pts p1->index 0, pts p1->index 1, &(p1->slope),
        &(p1->intercept), &(p1->direction));
    p1->failed = FALSE;
    p1->segment_used = FALSE;
    if(clockwise)
        count1 = -1;
    else
        count1 = 1;
}while(count1 != total_pts && count1 != 0);

* connect the first vertex structure to the last vertex of the polygon
and calculate the slope and intercept of the line segment the two
create. *

p1->forward = start_ptr;
start_ptr->back = p1;
p1 = start_ptr;
determine_slope(pts p1->back->index 0, pts p1->back->index 1,
    pts p1->index 0, pts p1->index 1, &(p1->slope),
    &(p1->intercept), &(p1->direction));

return;

```

```
*****
ROUTINE:          clockwis.c
*****
```

This routine calculates the area of the arbitrary planar polygon once it has been transformed to the 2D x-y plane. A negative area indicates a clockwise ordering of the vertices while a positive area indicates a negative ordering of vertices. A "0" is returned for counterclockwise ordering while a "1" is returned for clockwise ordering.

```
*****
```

```
clockwise_ordering(total_pts, pts)
```

```
int total_pts;
Coord pts[3];
```

```
{
```

```
float area;
int i, result;
```

```
area = 0.0;
```

```
for(i = 0; i < total_pts - 1; i++) {
    area = area + pts[i].x * pts[i+1].y;
```

```
area = area + pts[total_pts-1].x * pts[0].y;
```

```
for(i = 0; i < total_pts - 1; i++) {
    area = area - pts[i+1].x * pts[i].y;
```

```
area = area - pts[total_pts-1].x * pts[0].y;
```

```
if(area == 0)
    result = 0;
else
    result = 1;
```

```
return (result);
```

```
}
```

.....
ROUTINE: decompose.c
.....

Decompose the main polygon and as convex polygons are determined
these are passed through calls to the IRIS system to be filled.
.....

Object decompose polygon(total pts, pts, old pts)

int total pts;

Coord pts 3;

Coord old pts 3;

.....

boolean no_point_found, search_incomplete, adjust_needed, OK;

boolean skip_flag, skip_search;

int pt1, pt2, poly_count, value;

point *working_ptr;

clear_stack();

get_pt(total pts, pts);

get_pt(total pts, pts);

search_incomplete TRUE;

skip_search TRUE;

poly_count 0;

.....

Once an initial two points are taken from the concave polygon,
the process moves through the main chain to select out points
for constructing the simple convex polygons. Calls are made to
various routines to check for validity of pts that are accepted
into a polygon
.....

while(search_incomplete) {

 adjust_needed TRUE;

 OK TRUE;

 while(OK) {

 get_pt(total pts, pts);

 * we first check to see if we have made a complete loop of the
 vertices. *

 if(loop_completed()) {

 working_ptr = start_ptr;

```

    * find the structure in the linked list that matches the
    vertex on top of the stack *

while(working_ptr->index != stack TOP->index) {
    working_ptr = working_ptr->forward;
}

    * check to see if vertex creates a line segment with the
    vertex below it, on the stack, that intersects any edges
    of the concave polygon *

if(stack TOP-1->index != working_ptr->back->index) {
    value = intersecting_lines(pts stack TOP->index-0,
        pts stack TOP->index-1, pts stack TOP-1->index-0,
        pts stack TOP-1->index-1, stack TOP->slope,
        stack TOP->intercept, total_pts, pts);
}

if(value) {

    * if vertex creates an intersecting line segment then we
    remove it from the stack and reset the pointer to the
    linked list *

    current_ptr = start_ptr;
    while(current_ptr->index != stack TOP-1->index) {
        current_ptr = current_ptr->forward;
    }

    current_ptr = current_ptr->forward;
    release_pt();
    release_pt(); }

else {

    * since the line segment create is OK, we simply remove the
    vertex from the stack since it is the same as the one on
    the bottom of the stack, namely the beginning vertex *

    OK = FALSE;
    release_pt();
}

    * if we have not completed the loop then we must conduct the
    tests to ensure valid selection of vertices for a convex

```



```

    polygon *

else if(pt_out_of_bounds(total_pts, pts)) {
    release_pt();
}
}

* if at least three points have been selected then... *

if(valid_pts()) {

    * save the beginning and ending vertices for future reference *

    pt1= stack BOTTOM_index;
    pt2= stack TOP_index;

    * pass the vertices to IRIS system hardware for filling and display *

    define_polygon(old_pts);
    poly_count = 1;

    * if this is a normal decomposition and not a "fill in" polygon to
    cover holes left in the concave polygon then do the following *

    if(skip_search) {

        * set the flags that indicate next time through this loop we
        will be working on a "fill in" polygon *

        adjust_needed = FALSE;
        skip_search = FALSE;

        * adjust the pointers to the linked list so next time through
        the loop we have the start and end vertices of the previous
        polygon to begin working with *

        working_ptr = start_ptr;
        while(working_ptr->index != pt2) {
            working_ptr = working_ptr->forward;
        }

        * if the start and end vertices of the previous polygon are
        adjacent on the concave polygon then forget about building
        a "fill in" polygon *

        if(working_ptr->forward->index == pt1) {
            while(current_ptr->index == pt1) {

```

```

        current_ptr = current_ptr -> forward;
    }
    get_pt(total_pts, pts);
    current_ptr = working_ptr;
    get_pt(total_pts, pts); }
    else {
        adjust_needed = TRUE;
    }
}
}

```

* if the polygon is not fully decomposed yet we select
two new vertices to continue the decomposition process *

```

if(adjust_needed) {
    skip_search = TRUE;
    if(object_complete(total_pts))
        search_incomplete = FALSE;
    else {
        adjust_search_area(pts);
        clear_stack();
        get_pt(total_pts, pts);
        get_pt(total_pts, pts);
    }
}
}

return;
}

```

.....
ROUTINE: clear_stack.c
.....

This routine simply resets the stack pointer to -1. In this manner when the stack has its first item pushed on, the pointer will accurately reflect a value of 0. (BOTTOM OF STACK)
.....

```
clear_stack()
```

```
{
```

```
    TOP = -1;
```

```
}
```

```
*****
ROUTINE:          get_pt.c
*****
```

This retrieves the next point in the main chain, as identified by the current ptr, and places the point on the top of the stack. In doing so it increments the TOP variable. Also as the point is retrieved, the slope, intercept, and direction of the line segment it creates with the vertex below it on the stack is calculated.

```
get_pt(total_pts, pts)
```

```
int total_pts;
```

```
Coord pts[3];
```

```
{
```

```
    TOP = 1;
```

```
    if(TOP <= total_pts) {
```

```
        * select the vertex in the linked list that is currently pointed to *
```

```
        stack[TOP].index = current_ptr->index;
```

```
        * and then advance the list pointer *
```

```
        current_ptr = current_ptr->forward;
```

```
        if(TOP > 0) {
```

```
            * take the x, y, and z coordinates for both the vertex on top of
              the stack and the vertex just below it, to calculate the slope
              and y-intercept of the line segment they create *
```

```
            determine_slope(pts[stack[TOP-1].index][0], pts[stack[TOP-1].index][1],
                             pts[stack[TOP].index][0], pts[stack[TOP].index][1],
                             &stack[TOP].slope, &stack[TOP].intercept,
                             &stack[TOP].direction);
```

```
        }
```

```
    }
```

```
    else {
```

```
        printf("STACK overflow occurred while retrieving another point");
```

```
    }
```

```
    return;
```

```
}
```

.....
ROUTINE: release pt.c
.....

This routine removes the item on top of the stack by
decrementing the top of stack pointer TOP.
.....

release pt()
{

 if(TOP == BOTTOM)

 TOP--;

 else {

 printf("STACK underflow occured while trying to release a non-");

 printf("existence point.");

 }

 return;

}

```
.....
ROUTINE:          slopes.c
.....
```

This works through the pts array, and the stack array. By taking value of the TOP of stack and the point beneath it, the corresponding coordinates are obtained from the pts array and a slope, intercept and direction are calculated. These values are then stored in the stack.

```
.....
```

```
determine_slope(x1, y1, x2, y2, slope, intercept, direction)
```

```
Coord x1, y1, x2, y2:
```

```
float *slope:
```

```
Coord *intercept:
```

```
int *direction:
```

```
{
```

```
Coord dx, dy:
```

```
    * calculate the delta x and delta y for the to points *
```

```
dx = x2- x1;
```

```
dy = y2- y1;
```

```
    * if the line segment is vertical then use the value 99999.0 to
      indicate such (avoiding division by zero problems) *
```

```
if(dx == 0) {
```

```
    *slope = 99999.0;
```

```
    *intercept = x2; }
```

```
else {
```

```
    *slope = dy / dx;
```

```
    *intercept = y2 - (dy / dx) * x2;
```

```
}
```

```
    * based upon the changes in delta x and delta y we determine if we are
      traversing down a slope or up a slope *
```

```
if(dy < 0) {
```

```
    if(dx < 0)
```

```
        *direction = 1;
```

```
    else
```

```
        *direction = 0;
```

```
}
```

```
else {  
    if(dx < 0)  
        *direction = 0;  
    else  
        *direction = 1;  
}
```

```
return;
```

.....
ROUTINE: compare.c
.....

This routine determines if a point lies to the left or right of a line segment. This is done by using the x and y coordinates of the point with the slope, intercept, and direction of the line segment to create a parallel line segment. The y intercept (or in the case of vertical line, the x intercept) is used in conjunction with the direction of traversal along the line segment to find which side of the line segment, the point lies on.
.....

compare boundry(x1,y1,slope,intercept,direction)

Coord x1, y1;

float slope;

Coord intercept;

int direction;

{

float test_value;

int value;

 * if the line segment is vertical then we use the x-intercept to
 determine if a vertex lies to the left or right of another line
 segment *

if(slope == 99999.0)

 test_value = x1;

else

 test_value = y1- slope * x1;

 * based upon traversal up or down a sloping line we determine if
 a vertex is to the left or right of the line segment *

switch (direction) {

 case 0: if(test_value > intercept)

 value = 1;

 else

 value = 0;

 break;

 case 1: if(test_value > intercept)

 value = 1;


```
else  
    value = 0;  
    break;
```

```
return (value);
```

```
*****
ROUTINE:          pt_OOB.c
*****
```

This routine takes the vertex index from the top of the stack and uses its x, y coordinates to determine if the point lies out of bounds with respect to the convex polygon being created.

```
pt_out_of_bounds(total_pts, pts)
```

```
int total_pts;
```

```
Coord pts[3];
```

```
{
```

```
Coord x1, y1;
```

```
int ptr, value;
```

```
boolean not_finished;
```

```
point *working_ptr;
```

```
    * obtain the coordinates for the vertex on top of the stack *
```

```
x1 = pts[stack.TOP].index[0];
```

```
y1 = pts[stack.TOP].index[1];
```

```
ptr = TOP-1;
```

```
value = 0;
```

```
    * use the above coordinates to determine if the vertex lies to
    the left (out of bounds) with respect to any line segment
    created thus far in the selection of vertices *
```

```
while (ptr > BOTTOM && !value) {
```

```
    value = compare_boundary(x1,y1,pts[ptr].slope,pts[ptr].intercept,
    pts[ptr].direction);
```

```
    ptr--;
```

```
}
```

```
*****
If point is not out of bounds with any line segments created
then we check to see if the segment produced by this new point
addition causes the start point for the polygon to fall out of
bounds.
*****
```

```
if(!value) {
```

```
    x1 = pts[stack.BOTTOM].index[0];
```

```
    y1 = pts[stack.BOTTOM].index[1];
```

```

value= compare boundry(x1,y1,stack TOP .slope,stack TOP .intercept,
    stack TOP .direction);
if(value) {
    release pt();
    current ptr= current ptr- ·back;
    working ptr= start ptr;
}
}

```

.....

If the newly created line segment does not cause the initial pt of the developing polygon to fall out of bounds, then we check to see if the line segment intersects any line segments of the concave polygon.

.....

```

if(!value) {
    working ptr= start ptr;
    while(working ptr- ·index != stack TOP .index) {
        working ptr= working ptr- ·forward;
    }
    if(stack TOP-1 .index != working ptr- ·back- ·index) {

        * we use the coordinates for the vertex at the top of stack
        and the vertex below it to create a line segment which we
        then check for intersection with any of the edges of the
        original concave polygon *

        value= intersecting_lines(pts stack TOP .index 0 ,
            pts stack TOP .index 1 , pts stack TOP-1 .index 0 ,
            pts stack TOP-1 .index 1 , stack TOP .slope,
            stack TOP .intercept, total pts, pts);
    }
}

```

.....

If the newly created line segment does not intersect any line segments of the concave polygon then we check to see if the line segment of the original polygon, that the top of stack point heads, causes the point below top of stack to fall out.

.....

```

if(!value) {
    if(current ptr- ·back- ·back- ·index != stack TOP-1 .index) {
        x1= pts stack TOP-1 .index 0 ;
        y1= pts stack TOP-1 .index 1 ;
        value= compare boundry(x1,y1,current ptr- ·back- ·slope,

```

```

        current_ptr ← back ← intercept.
        current_ptr ← back ← direction);
    }
}

```

.....

If the point is determined to be out of bounds, then the appropriate pointers are adjusted to continue the decomposition process. Otherwise the pt is a valid addition to the stack

.....

```

if(value) {
    working_ptr ← start_ptr;
    not_finished ← TRUE;
    do {
        if(working_ptr.index = stack.TOP.index) {
            not_finished ← FALSE;
            if(working_ptr.failed = FALSE)
                working_ptr.failed ← TRUE;
        }
        else {
            working_ptr ← working_ptr.forward;
        }
    } while(not_finished);
}

return(value);
}

```

.....
ROUTINE: loop_completed
.....

This routine checks to see if the vertices of the concave polygon have been completely traversed while developing a single convex polygon. This is done when the vertex on top of the stack is the same vertex on the bottom of the stack. When this occurs a value of 1 is returned.
.....

```
int loop_completed()
```

```
int value;
```

```
if(TOP == -1) {
```

```
  if(stack[TOP].index == stack[BOTTOM].index) {
```

```
    value = 1; }
```

```
  else {
```

```
    value = 0;
```

```
  }
```

```
}
```

```
else {
```

```
  printf("Error in stack index while checking TOP & BOTTOM values");
```

```
  value = -1;
```

```
}
```

```
return (value);
```

```
*****
ROUTINE:          adjust.c
*****
```

This routine searches the circular list of vertices, checking the various condition flags, to locate a vertex or line segment of the original polygon which has not been utilized. As one is located, the list's currency pointer is moved to that structure in the list so that further polygon decomposition may continue.

```
adjust_search_area(pts)
```

```
Coord pts = 3:
```

```
{
```

```
    boolean done;
```

```
    point *p1;
```

```
    done = 0;
```

```
    p1 = start_ptr;
```

```
    do {
```

```
        if(p1->failed == 1)
```

```
            /* check to see if the line segment to either side of the vertex
             * has been used in a previously developed polygon. */
```

```
        if(!(p1->forward->segment_used) && !(p1->segment_used)) {
```

```
            current_ptr = p1;
```

```
            p1->failed = 0;
```

```
            done = 1; }
```

```
        else {
```

```
            p1 = p1->forward;
```

```
        }
```

```
        else {
```

```
            p1 = p1->forward;
```

```
        }
```

```
    } while(!done && p1 != start_ptr);
```

```
    return;
```

```
}
```

```
*****
ROUTINE:      valid_pts.c
*****
```

```
This routine checks to ensure that at least 3 vertices have
been determined for the convex polygon.  If not then the
value of 0 is returned.
*****
```

```
boolean valid_pts()
{
```

```
    int value;
```

```
    if(TOP == 2)
```

```
        value = 1;
```

```
    else
```

```
        value = 0;
```

```
    return (value);
```

```
}
```

```
*****
ROUTINE:          define_poly.c
*****
```

This routine takes the vertices accumulated on the stack and uses the IRIS features pmv and pdr to actually perform the display of the polygon created. The index for each vertex is used to access the original array of points to get the x, y and z coordinates used.

```
*****
```

```
define_polygon(pts)
```

```
Coord pts 3:
```

```
{
```

```
int count;
point *track_ptr;
```

```
track_ptr = start_ptr;
```

```
  * pass the starting vertex for the newly created convex
  polygon to the IRIS hardware with a point move command *
```

```
pmv(pts stack BOTTOM.index 0,
    pts stack BOTTOM.index 1,
    pts stack BOTTOM.index 2);
```

```
  * locate this vertex in the linked list *
```

```
while(track_ptr->index != stack BOTTOM.index) {
  track_ptr = track_ptr->forward;
}
```

```
  * set the flag to indicate the vertex has been used
  in a convex polygon *
```

```
if(track_ptr->back->index == stack TOP.index)
  track_ptr->segment_used = TRUE;
```

```
  * for each vertex of the convex polygon, pass its
  coordinates to IRIS hardware with the point draw
  command *
```

```
count = 1;
while(count <= TOP) {
  while(track_ptr->index != stack count.index) {
```



```

    track_ptr= track_ptr- -forward;
}
if(track_ptr->back->index == stack_count-1.index)
    track_ptr->segment_used= TRUE;
pdr(pts_stack_count.index 0 ,
    pts_stack_count.index 1 ,
    pts_stack_count.index 2 );
count = 1;
}

```

' pass the command to the IRIS hardware that the
fill the completed convex polygon '

```
pclos();
```

```
clear_stack();
```

```
return;
```

```
}
```

```
*****
ROUTINE:          obj_complet.c
*****
```

```
This routine checks each vertex and edge of the original
concave polygon to see if they have all been utilized in the
process of decomposition. If so a value of 1 is returned.
*****
```

```
int object_complete(total pts)
```

```
int total pts;
```

```
{
```

```
point *p1;
```

```
int count, value;
```

```
count = 0;
```

```
value = 1;
```

```
p1 = start_ptr;
```

```
/* search through the linked list of structures, for the
vertices, and return the index of the first vertex that
creates an edge of the concave polygon not yet utilized */
```

```
do {
```

```
if(p1->segment_used) {
```

```
    p1 = p1->forward;
```

```
    count ++ 1; }
```

```
else {
```

```
    value = 0;
```

```
    }
```

```
} while(count != total pts && value == 1);
```

```
return (value);
```

```
}
```

```
.....
ROUTINE:      intersecting.c
.....
```

This routine takes two vertices and the slope and intercept of the line segment they create to determine if it intersects any of the edges of the original polygon. If so then a value of 1 is returned.

```
.....
```

```
intersecting lines(x2, y2, x1, y1, slope, intercept, total pts, pts)
```

```
Coord x2, y2, x1, y1:
```

```
float slope:
```

```
Coord intercept:
```

```
int total pts:
```

```
Coord pts 3 :
```

```
{
```

```
point *p1:
```

```
float x intersect, y intersect, x min, x max, y min, y max, fudge:
```

```
int value:
```

```
    * define a value to offset round off error *
```

```
fudge= 0.000001;
```

```
value = 0;
```

```
p1 = start ptr:
```

```
    * for each edge of the concave polygon we check if either vertex
    lies on the edge. If not then we determine the intersection
    of the line, defined by the edge, with the line defined by the
    two vertices. Finally we determine if this intersection lies on
    both line segments. If so then we have found an actual intersection. *
```

```
do {
```

```
    * check if first vertex lies on the polygon's edge being examined *
```

```
    if(((x1 != pts p1->index 0) || (y1 != pts p1->index 1)) &&
        ((x1 != pts p1->back->index 0) || (y1 != pts p1->back->index 1))) {
```

```
        * check if second vertex lies on the edge *
```

```
        if(((x2 != pts p1->index 0) || (y2 != pts p1->index 1)) &&
            ((x2 != pts p1->back->index 0) || (y2 != pts p1->back->index 1))) {
```

```

/* if the lines are not parallel then ... */

if(slope != p1->slope) {

    /* if the line created by the vertices is vertical */

    if(slope == 99999.0) {
        /* determine the coordinates of the intersection */
        x intersect = x2;
        y intersect = p1->slope * x intersect + p1->intercept;

        /* if the edge of the polygon is vertical */

    else if(p1->slope == 99999.0) {
        /* determine the coordinates of the intersection */
        x intersect = pts p1->index 0;
        y intersect = slope * x intersect + intercept;

        /* if neither line is vertical */

    else {
        /* determine the coordinates of the intersection */
        x intersect = (intercept - (p1->intercept)) / ((p1->slope) - slope);
        y intersect = slope * x intersect + intercept;
    }

    /* determine the x range that the intersection must occur in
       to lie on the line segment created by the two vertices */

    max = min(x2,x1,&x_max,&x_min);

    /* check if the intersection falls within this range */

    if((x intersect >= x_min-fudge)&&(x intersect <= x_max + fudge)) {

        /* since the intersection is within this x range we now determine
           the x range for the edge of the concave polygon */

        max = min(pts p1->index 0, pts p1->back->index 0, &x_max, &x_min);

        /* check if the intersection falls within this range */

        if((x intersect >= x_min-fudge)&&(x intersect <= x_max + fudge)) {

            /* now that the intersection falls within the x range of both
               line segments, we must calculate the y range for each

```

```

        segment and perform the checks *

    * y range for the vertices line segment *

    max = min(y2,y1,&y_max,&y_min);

    if((y_intersect < y_min-fudge)&&(y_intersect > y_max+fudge)) {

        * y range for the concave polygon edge *

        max = min(pts[p1-1].pts[p1-1].back-1,&y_max,&y_min);
        if((y_intersect < y_min-fudge)&&(y_intersect > y_max+fudge)) {
            value = 1;
            * the intersection exists for the actual line segments and
              therefore the vertex on top of the stack must be removed *
        }
    }
}
}
}
p1 = p1-forward;
} while((p1 != start_ptr)&&(value != 0));

return(value);
}

```

```
.....  
ROUTINE:          max_min.c  
.....
```

```
Given two float values, p1 and p2, this routine determines  
which is larger of the two.  
.....
```

```
max_min(p1, p2, max, min)
```

```
Coord p1, p2, *max, *min;
```

```
{  
  
    if(p1 > p2) {  
        *max = p2;  
        *min = p1; }  
    else {  
        *max = p1;  
        *min = p2;  
    }  
}
```

```
return;
```

```
}
```

INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Technical Information Center Cameron Station Alexandria, Virginia 22304-6145	2
2. Library, Code 0142 Attn: Library, Code 0142 Naval Postgraduate School Monterey, California 93943-5002	2
3. Chairman, Code 52 Department of Computer Science Naval Postgraduate School Monterey, California 93943-5000	1
4. Computer Technology Curricular Officer, Code 37 Naval Postgraduate School Monterey, California 93943-5000	1
5. Dr. Michael J. Zyda, Code 52Zk Department of Computer Science Naval Postgraduate School Monterey, California 93943-5000	2
6. Dr. Robert B. McGhee, Code 52Mz Department of Computer Science Naval Postgraduate School Monterey, California 93943-5000	1
7. Capt Jeffrey H. Potts C/O Alexander Murphy III 12701 Skipper Lane Hudson, Fla. 33562	8

END

4-87

DTIC